



DATE	SYM	REVISION RECORD	DR.	CK.

FEATURES

- 50/25 H.P 1800/900 RPM. SANITARY DRIVE MOTOR
- 208 VOLT 60 HERTZ 3 PHASE W/FULL MAGNETIC CONTROL & 115 VOLT CONTROL CIRCUIT
- SOLID STAINLESS STEEL AGITATOR & SHAFT
- SOLID STAINLESS STEEL BOWL SHEET & COVER
- SOLID STAINLESS STEEL BOWL ENDS
- SOLID STAINLESS STEEL D.E. JACKET - FREON 22
- SOLID STAINLESS STEEL HOUSINGS & END DOORS
- AGITATOR SPEEDS 35 RPM LOW 70 RPM HIGH
- POWER BOWL TILT - MECHANICAL
- PNEU. STAINLESS FLOUR GATE W/HEAVY GA. STAIN S. LIDE
- SANITARY REMOVABLE PACKING SYSTEM
- DOUBLE AUTOMATIC PLUG IN TYPE TIMERS
- HIGH & LOW SPEED JOG OPERATION
- NEMA 12 DUST TIGHT ENCLOSURE W/CIRCUIT BREAKER
- ALLEN BRADLEY ELECTRICALS W/EAGLE RELAYS
- AUTOMATIC CHAIN OILER MOUNTED EXTERNALLY
- TRITCH TRIPLE SPROCKETS AND CHAIN
- UNIVERSAL COUPLING
- FAH. - CENT. DIAL TYPE BOWL THERMOMETER
- BOWL FTG'S ONLY FOR REFRIG. W/8 TON EXP. VALVE
- REMOVABLE HINGED TOP REAR WRAPPER SHEET
- TAPERED KEYS IN AGITATOR SPROCKETS
- SPECIAL LOWER THERMOMETER PROBE LOCATION
- SPECIAL HEAVY DUTY IDLER ADJUSTMENT
- CUTOUT IN FRAME UPRIGHT FOR AXLE TO BE COVERED
- TAPER CUT AGITATOR WIPER BLADE
- DOUBLE KEY IN AGITATOR

HARTIGAN & VAN WAGNER, INC.

P.O. No. 1180

BELLACICCO & SONS INC.
 PEELLESS AMBASSADOR HIGH SPEED MIXER
 MODEL 555
 FACTORY ORDER No. 79036

TOLERANCES (EXCEPT AS NOTED)		SCALE		DRAWN BY: M.H.	
DECIMAL				APPROVED BY	
FRACTIONAL		TITLE CERTIFIED DATA SHEET			
ANGULAR		DATE 12-17-79	DRAWING NUMBER 5JB-209		